


Glass mash 112

Item No. 35.011, 35.014

- Especially for planking made of clayboards heavy (LEMIX)



Surface reinforcement for clay adhesive and reinforcing mortar and all clay plaster. ClayTec glass mash its a gauze made of glass fibre yarn/roving, enhanced with polymer finishing for scrim. It is tensile, very fine and particularly easy to work with.

 **ClayTec**[®]

GERMANY
© ClayTec GmbH & Co. KG
Nettetaler Straße 113-117
D-41751 Viersen-Boisheim
+49 (0)2153 918-0
service@claytec.com
claytec.com

2025/3
Changes and errors excepted.
Current version available at
claytec.com

Glass mash 112

Item No. 35.011, 35.014

Application Surface reinforcement for planking clayboard heavy (LEMIX) ClayTec 09.014 and 09.015.

Composition Gauze made of glass fibre yarn/roving, enhanced with polymer finishing for scrim. Weight approx. 112 g/m², warp/weft approx. 16/15 fibres per 10 cm, mesh size approx. 5.0 x 5.5 mm. Alkali resistant.

Form of delivery On rolls, in surface reinforcement; width 100 cm, length 100 m (LEMIX 35.011) and 35 m (LEMIX 35.014).

Storage Can be stored for at least three years if kept dry, well-ventilated and protected against direct sunlight.

Amount required Surface reinforcement: equal to m² plaster surface plus an additional 10-20% extra for waste and overlapping.

Method of use The mesh is laid on the mortar while it is still freshly applied and plastic, and rubbed in with a sponge board or similar. Approx. 10 cm overlap must be provided in areas around joints.

Claims for compensation that do not result from factory mixing errors are excluded. Subject to change and errors excepted. As of 2025/3.